Wireless Bell Kit

Installation Instructions

nstallation instructions






Figure 1 - Push Button (Transmitter/Remote)




Figure 2 - Bell (Receiver)

Installing Battery in the Bell Push (Transmitter/Remote)

- 1. Remove the front cover of the remote by pushing a flat blade screwdriver into the slot at the bottom (see Fig.1).
- Place the 12V 23A battery into the battery slot and close the Transmitter.

Note: The bell and the remote have been paired during production. Once the battery is installed in the remote and bell is powered on, press the push button to ensure that the remote causes the bell to ring.

IF THE BELL DOES NOT RING, SEE TROUBLESHOOTING. TO CHANGE THE DEFAULT TUNE, FOLLOW THE STEPS BELOW

Pairing & Tune Selection (See Figure 3)

- 1. The package is already paired. If you need to pair a remote and a bell, or change the tune, press the Pairing button ላᢀ on the bell for 4-5 seconds and you will hear a double beep. The bell is in Pairing state.
- Press the Tune Selection button ♪ on the bell to select the tune you want for the remote.
- After the tune has been selected, press the button on the remote once. The bell will play a beep to indicate that the new remote is saved with the selected tune.
- 4. To complete pairing, press the Pairing button ্বত) on the bell.
- 5. If you want to pair more remotes, repeat the above process one by one for each remote.


Unpairing:

- . To clear all codes on a bell and unpair it with all remotes, first remove the battery out of the bell.
- 2. Then, hold the Tune Selection Button ∫ and simultaneously put the battery back into the bell. Keep holding the Tune Selection button ∫ for 6-8 seconds and the bell will be reset.

Volume Adjustment:

24. Room No. 2

There are four volume levels on this bell. Press the volume adjustment button (1)) to set the bell at your desired volume.





3D - Complete Pairing by again pressing the Pairing Button (1))

Figure 3 - Pairing Bell and Remote

Troubleshooting:

If the bell does not work,

- Make sure to remove the insulating paper strip from the remote.
- 2. Verify battery installation is correct, noting polarity.
- 3. Try <u>unpairing</u> and <u>pairing</u> the remote back again using the above-mentioned steps.
- 4. Try a fresh battery in the remote.
- Ensure that the remote is not mounted on metal, near metal studs or on a hot surface.
- 6. Try a new location for the bell.

pressfit



An Unparalleled Choice of 48 Tunes Available

1. House Bell 1	25. Room No. 3
2. House Bell 2	26. Room No. 4
3. Airplane DD	27. Room No. 5
4. Electronic DD	28. Room No. 6
5. Basic DD 1	29. Room No. 7
6. Gong DD	30. Room No. 8
7. Westminster DD	31. Melody 1
8. Hotel Call Chime	32. Melody 2
9. Hotel Call Chime 2	33. Melody 3
10. Elevator Chime	34. Beethoveen - Fur Elise
11. Airport Announcement	35. Mozart - Rondo alla Turca
12. Marimba 1	36. Jingle Bells - 1
13. Marimba 2	37. Jingle Bells - 2
14. Marimba 3	38. Merry Christmas
15. Marimba 4	39. Oh, Susanna
16. Please Open the Door - Male	40. Super Mario Bros.
17. Please Open the Door - Female	41. Gayatri Mantra - Female
18. Next Patient Please - Male	42. Gayatri Mantra - Male
19. Next Patient Please - Female	43. Om Namah Shivaay
20. Please Come In	44. Hare Krishna
21. I Need Assistance - Male	45. Hare Rama
22. I Need Assistance - Female	46. Buddham Saranam Gacchami
23. Room No. 1	47. Azan - Short

Functional range may be adversely affected by one or more of the following factors: weather, radio frequency interference, low remote battery and obstructions between the remote and the hell

For extra bell receivers and remotes, contact us at sales@pressfitindia.com or through www.pressfitindia.com.

48. Azan - Long