


Technical Data Sheet




Code		Product	Nominal Overall Length (L) (±3%)		Strap Width (W) (±0.15mm)		Max. Bundle Cable Diameter		Min. Loop Tensile Strength		Std. Pkg.	
			mm	inch	mm	inch	mm	inch	kgf	lbs	(pcs/pkt)	
Miniature Series												
M3	93013	100 x 1.8	100.0	3.9	1.80	0.07	20	0.79	8.2	18	100	
M1	93031	60 x 2.0	60.0	2.4	2.00	0.08	10	0.39	8.2	18	100	
M4	93043	100 x 2.2	100.0	3.9	2.20	0.09	20	0.79	8.2	18	100	
M6	93044	150 x 2.2	150.0	5.9	2.20	0.09	35	1.38	8.2	18	100	
M2	93052	75 x 2.5	75.0	3.0	2.50	0.10	16	0.63	8.2	18	100	
M5	93053	100 x 2.5	100.0	3.9	2.50	0.10	20	0.79	8.2	18	100	
M7	93054	150 x 2.5	150.0	5.9	2.50	0.10	35	1.38	8.2	18	100	
M8	93055	200 x 2.5	200.0	7.9	2.50	0.10	45	1.77	8.2	18	100	
Intermediate Series												
I4	93125	300 x 3.3	300.0	11.8	3.30	0.12	75	2.95	18.0	40	100	
I1	93132	150 x 3.6	150.0	5.9	3.60	0.14	35	1.38	18.0	40	100	
I2	93133	200 x 3.6	200.0	7.9	3.60	0.14	45	1.77	18.0	40	100	
I3	93134	250 x 3.6	250.0	9.8	3.60	0.14	60	2.36	18.0	40	100	
I5	93135	300 x 3.6	300.0	11.8	3.60	0.14	75	2.95	18.0	40	100	
I6	93136	350 x 3.6	350.0	13.8	3.60	0.14	90	3.54	18.0	40	100	
Standard Series												
S2	93213	250 x 4.2	250.0	9.9	4.20	0.16	60	2.36	22.7	50	100	
S1	93222	200 x 4.8	200.0	7.9	4.80	0.19	45	1.77	22.7	50	100	
S3	93223	250 x 4.8	250.0	9.8	4.80	0.19	60	2.36	22.7	50	100	
S4	93225	300 x 4.8	300.0	11.8	4.80	0.19	75	2.95	22.7	50	100	
S5	93226	364 x 4.8	364.0	14.3	4.80	0.19	95	3.74	22.7	50	100	
S6	93228	400 x 4.8	400.0	15.7	4.80	0.19	100	3.54	22.7	50	100	
S7	93227	450 x 4.8	450.0	17.7	4.80	0.19	115	4.53	22.7	50	100	
Heavy Duty Series												
H1	93311	200 x 7.6	200.0	7.9	7.60	0.29	45	1.77	54.0	119	100	
H2	93313	300 x 7.6	300.0	11.8	7.60	0.29	75	2.95	54.0	119	100	
H3	93314	364 x 7.6	364.0	14.3	7.60	0.29	95	3.74	54.0	119	100	
H4	93315	430 x 7.6	460.0	16.9	7.60	0.29	110	4.33	54.0	119	100	
H5	93316	530 x 7.6	530.0	20.9	7.60	0.29	140	5.51	54.0	119	100	
Extra Heavy Duty Series												
X1	93413	630 x 8.8	630.0	24.8	8.80	0.35	175	6.89	59.0	130	100	
X2	93414	710 x 8.8	710.0	28.0	8.80	0.35	200	7.87	59.0	130	100	

Material: Nylon-6,6 (UL94V2, CE & RoHS Compliant)


Available Colours: Natural - For Indoor Use, Black - For Indoor & Outdoor Use
Other Colours Can Be Manufactured For Special Requirements.
*Product codes are 6 digits long. The last digit stands for the colour: 0 - Black 1 - White
For e.g. The code for 60 x 2.0 Black will be- 93031 + 0 = 930310.

Imp. Note: the Min. Tensile Strength mentioned above is as per general Underwriters Laboratories (UL) standards. PressFit's Nylon-6,6 Cable Ties are manufactured to these standards but since certification is expensive, they may not all be certified so as to keep the product prices optimal. It does not mean that the quality is poorer. In fact, the general Tensile Strength of PressFit's Nylon-6,6 Cable Ties is much higher than the min. specifications mentioned above.


Smooth, Round Edges




High Tensile Strength



Curved Tip for Speedy Installation



More Teeth Per Inch



1800-2121-770



pressfitindia

[https://](https://pressfitindia.com)

pressfitindia.com